2441 10 10209

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(4-)) International Publication Number: WO 99/50890
H01L 21/00 A1 (43	3) International Publication Date: 7 October 1999 (07.10.99)
	(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: METHOD FOR MAKING MULTILAYER THIN-FILM ELECTRONICS

1 (57) Abstract

Multilayer thin-film electronics are manufactured at high speed, even while the various component functions are manufactured separately under conditions tailored to optimize component performance and yield. Each function or group of functions is fabricated on a separate flexible substrate. These flexible substrates are bonded to each other using adhesive films that are anisotropic electrical conductors or optical light guides. The bonding is performed by laminating the flexible substrates to each other in a continuous process, using the anisotropic conductor as the bonding layer.